



FAG

16052-M-C3

Deep groove ball bearing

Deep groove ball bearing 160...-M, single row, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Sealing	Without	Not sealed
Cage	M	Solid brass cage, rolling element guided
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	400 mm	Outside diameter
B	44 mm	Width
C _r	237.000 N	Basic dynamic load rating, radial
C _{0r}	310.000 N	Basic static load rating, radial
C _{ur}	10.200 N	Fatigue load limit, radial
n _G	2.850 1/min	Limiting speed
n _{gr}	1.960 1/min	Reference speed
≈m	21,6 kg	Masa



Mounting dimensions

d a min	272,4 mm	Minimum diameter shaft shoulder
D a max	387,6 mm	Maximum diameter of housing shoulder
r a max	2,5 mm	Maximum fillet radius

Dimensions

r min	3 mm	Minimum chamfer dimension
D 1	351,2 mm	Shoulder diameter outer ring
d 1	310 mm	Shoulder diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	200 °C	Operating temperature max.

Calculation factors

f 0	16,4	Calculation factor
-----	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe