


**212-XL-KRR**

Deep groove ball bearing

Radial insert ball bearings 2..-KRR, cylindrical outer ring, inner ring for fit, R seals on both sides

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Type of Seal	KRR	Lip seals on both sides
--------------	-----	-------------------------

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	110 mm	Outside diameter
B	36 mm	Width
C _r	56.000 N	Basic dynamic load rating, radial
C _{0r}	36.000 N	Basic static load rating, radial
≈m	1,019 kg	Masa

Dimensions

D ₁	95,75 mm	Outside diameter seal
C	22 mm	Width, outer ring
C ₂	29,1 mm	Sealing total width
d ₁	76,48 mm	Rib diameter inner ring
r _{min}	1,5 mm	Minimum chamfer dimension

Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.



Calculation factors

f ₀	14,3	Calculation factor
----------------	------	--------------------

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie dożywotnie, bezobsługowe
-  Smarowanie smarem
-  Uszczelnienie dwustronne