



FAG



21319-E1-XL-K-TVPB-C3

Spherical Roller Bearing

Spherical roller bearings 213..-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	TVPB	Plastic cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	95 mm	Bore diameter
D	200 mm	Outside diameter
B	45 mm	Width
C _r	425.000 N	Basic dynamic load rating, radial
C _{0r}	450.000 N	Basic static load rating, radial
C _{ur}	48.500 N	Fatigue load limit, radial
n _G	4.600 1/min	Limiting speed
n _{gr}	3.250 1/min	Reference speed
≈m	6,413 kg	Masa



Mounting dimensions

$d_{a \min}$	109 mm	Minimum diameter shaft shoulder
$D_{a \max}$	186 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius
$B_{a \min}$	7 mm	Minimum cavity width of the sleeve
$d_{a \max}$	124 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	102 mm	Minimum cavity diameter of the sleeve

Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
D_1	169,4 mm	Bore diameter outer ring
d_2	124,3 mm	Raceway diameter of the inner ring
d_s	4,8 mm	Diameter lubrication hole
n_s	9,5 mm	Width of lubricating groove

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

e	0,22	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	3,04	Dynamic axial load factor
Y_2	4,53	Dynamic axial load factor
Y_0	2,97	Static axial load factor

Additional information

H319	Adapter sleeve
AHX319	Withdrawal sleeve



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna