






FAG

2217-K-M>N

Self-aligning ball bearing

Self-aligning ball bearing 22..-K-M, tapered bore taper 1:12, solid brass cage

Informacje techniczne



Twoja aktualna wersja produktu

Version code	>N	Not marked on bearing
Bore type	K	Tapered, taper 1:12
Sealing	Without	Not sealed
Cage	M	Solid brass cage, ball guided
Tolerance class	PN	Normal (ISO 492:2023)
Radial internal clearance	CN (Group N)	Normal internal clearance
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	85 mm	Bore diameter
D	150 mm	Outside diameter
B	36 mm	Width
C _r	59.000 N	Basic dynamic load rating, radial
C _{0r}	23.600 N	Basic static load rating, radial
C _{ur}	1.380 N	Fatigue load limit, radial
n _G	7.200 1/min	Limiting speed
n _{gr}	5.200 1/min	Reference speed
≈m	2,67 kg	Masa



Mounting dimensions

d a min	96 mm	Minimum diameter shaft shoulder
d a max	102 mm	Maximum diameter shaft shoulder
D a max	139 mm	Maximum diameter of housing shoulder
d b min	91 mm	Minimum cavity diameter of the sleeve
B a min	12 mm	Minimum cavity width of the sleeve
r a max	2 mm	Maximum fillet radius

Dimensions

r min	2 mm	Minimum chamfer dimension
D 1	129,97 mm	Shoulder diameter outer ring
d 1	105,2 mm	Shoulder diameter inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	150 °C	Operating temperature max.

Calculation factors

e	0,26	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y 1	2,46	Dynamic axial load factor
Y 2	3,8	Dynamic axial load factor
Y 0	2,57	Static axial load factor

Additional information

H317	Adapter sleeve
------	----------------



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna