



FAG

22218-E1-XL-K-C2

Spherical Roller Bearing

Spherical roller bearings 222...-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                    |
|---------------------------|--------------|------------------------------------|
| Design                    | E1           | Without central rip                |
| Bore type                 | K            | Tapered, taper 1:12                |
| Cage                      | JPA          | Sheet metal cage                   |
| Radial internal clearance | C2 (Group 2) | Internal clearance smaller than CN |
| Relubrication feature     | Standard     |                                    |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 90 mm       | Bore diameter                     |
| D               | 160 mm      | Outside diameter                  |
| B               | 40 mm       | Width                             |
| C <sub>r</sub>  | 345.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 375.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 43.500 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 5.200 1/min | Limiting speed                    |
| n <sub>gr</sub> | 3.400 1/min | Reference speed                   |
| m               | 3,26 kg     | Masa                              |



### Mounting dimensions

|              |        |                                       |
|--------------|--------|---------------------------------------|
| $d_{a \min}$ | 101 mm | Minimum diameter shaft shoulder       |
| $d_{a \max}$ | 106 mm | Maximum diameter of shaft shoulder    |
| $D_{a \max}$ | 149 mm | Maximum diameter of housing shoulder  |
| $r_{a \max}$ | 2 mm   | Maximum recess radius                 |
| $d_{b \min}$ | 96 mm  | Minimum cavity diameter of the sleeve |
| $B_{a \min}$ | 10 mm  | Minimum cavity width of the sleeve    |

### Dimensions

|            |          |                                    |
|------------|----------|------------------------------------|
| $r_{\min}$ | 2 mm     | Minimum chamfer dimension          |
| $D_1$      | 143,9 mm | Bore diameter outer ring           |
| $d_2$      | 106,1 mm | Raceway diameter of the inner ring |
| $d_s$      | 3,2 mm   | Diameter lubrication hole          |
| $n_s$      | 6,5 mm   | Width of lubricating groove        |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 200 °C | Operating temperature max. |

### Calculation factors

|       |      |                                                                                      |
|-------|------|--------------------------------------------------------------------------------------|
| $e$   | 0,23 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 2,9  | Dynamic axial load factor                                                            |
| $Y_2$ | 4,31 | Dynamic axial load factor                                                            |
| $Y_0$ | 2,83 | Static axial load factor                                                             |

### Additional information

|        |                   |
|--------|-------------------|
| H318   | Adapter sleeve    |
| AHX318 | Withdrawal sleeve |



## Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna