

FAG



22218-E1A-XL-K-M-C3

Spherical Roller Bearing

Spherical roller bearing 222...-E1A-XL-K-M,
symmetric 2 outer ribs

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	90 mm	Bore diameter
D	160 mm	Outside diameter
B	40 mm	Width
C _r	345.000 N	Basic dynamic load rating, radial
C _{0r}	375.000 N	Basic static load rating, radial
C _{ur}	43.500 N	Fatigue load limit, radial
n _G	5.200 1/min	Limiting speed
n _{gr}	3.400 1/min	Reference speed
≈m	3,275 kg	Masa



Mounting dimensions

$d_{a\ min}$	101 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	149 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2 mm	Maximum recess radius
$d_{a\ max}$	106 mm	Maximum diameter of shaft shoulder
$d_{b\ min}$	96 mm	Minimum cavity diameter of the sleeve
$B_{a\ min}$	10 mm	Minimum cavity width of the sleeve

Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
D_1	143,9 mm	Bore diameter outer ring
d_2	106,1 mm	Raceway diameter of the inner ring
d_s	3,2 mm	Diameter lubrication hole
n_s	6,5 mm	Width of lubricating groove

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

e	0,23	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,9	Dynamic axial load factor
Y_2	4,31	Dynamic axial load factor
Y_0	2,83	Static axial load factor

Additional information

H318	Adapter sleeve
AHX318	Withdrawal sleeve



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość dynamiczna