



**FAG****22236-E1A-XL-K-M-C3**

Spherical Roller Bearing

Spherical roller bearing 222...-E1A-XL-K-M,
symmetric 2 outer ribs**X-life**

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	180 mm	Bore diameter
D	320 mm	Outside diameter
B	86 mm	Width
C _r	1.360.000 N	Basic dynamic load rating, radial
C _{0r}	1.680.000 N	Basic static load rating, radial
C _{ur}	153.000 N	Fatigue load limit, radial
n _G	2.470 1/min	Limiting speed
n _{gr}	1.670 1/min	Reference speed
≈m	28,17 kg	Masa



Mounting dimensions

$d_{a\ min}$	197 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	303 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum recess radius
$d_{a\ max}$	211 mm	Maximum diameter of shaft shoulder
$d_{b\ min}$	191 mm	Minimum cavity diameter of the sleeve
$B_{a\ min}$	18 mm	Minimum cavity width of the sleeve

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
D_1	285,9 mm	Bore diameter outer ring
d_2	211,3 mm	Raceway diameter of the inner ring
d_s	9,5 mm	Diameter lubrication hole
n_s	17,7 mm	Width of lubricating groove

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

e	0,25	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,71	Dynamic axial load factor
Y_2	4,04	Dynamic axial load factor
Y_0	2,65	Static axial load factor

Additional information

H3136	Adapter sleeve
AH2236G	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość dynamiczna