



FAG



22240-BE-XL-K-C4

Spherical Roller Bearing

Spherical roller bearings 222...-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	JPB	Sheet metal cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	200 mm	Bore diameter
D	360 mm	Outside diameter
B	98 mm	Width
C _r	1.520.000 N	Basic dynamic load rating, radial
C _{0r}	1.990.000 N	Basic static load rating, radial
C _{ur}	180.000 N	Fatigue load limit, radial
n _G	2.330 1/min	Limiting speed
n _{gr}	1.510 1/min	Reference speed
m	41,72 kg	Masa



Mounting dimensions

$d_{a\ min}$	217 mm	Minimum diameter shaft shoulder
$d_{a\ max}$	234 mm	Maximum diameter of shaft shoulder
$D_{a\ max}$	343 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum recess radius
$d_{b\ min}$	212 mm	Minimum cavity diameter of the sleeve
$B_{a\ min}$	24 mm	Minimum cavity width of the sleeve

Dimensions

r_{min}	4 mm	Minimum chamfer dimension
D_1	310,9 mm	Bore diameter outer ring
d_2	238,2 mm	Raceway diameter of the inner ring
d_s	9,5 mm	Diameter lubrication hole
n_s	17,7 mm	Width of lubricating groove

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Calculation factors

e	0,26	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,57	Dynamic axial load factor
Y_2	3,83	Dynamic axial load factor
Y_0	2,52	Static axial load factor

Additional information

H3140	Adapter sleeve
AH2240	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna