



FAG


22326-E1-XL-T41A

Spherical Roller Bearing

Spherical roller bearing 223...-E1-XL-T41A, symmetric with cage guidance ring

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1	Without central rip
Bore type	Z	Cylindrical
Cage	JPA	Sheet metal cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication feature	Standard	
Spherical roller bearing for vibrating screens	T41A	For vibrating screens

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	280 mm	Outside diameter
B	93 mm	Width
C _r	1.250.000 N	Basic dynamic load rating, radial
C _{0r}	1.370.000 N	Basic static load rating, radial
C _{ur}	120.000 N	Fatigue load limit, radial
n _G	2.650 1/min	Limiting speed
n _{gr}	1.820 1/min	Reference speed
≈m	27,237 kg	Masa



Mounting dimensions

$d_{a\ min}$	147 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	263 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum recess radius

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
D_1	239,5 mm	Bore diameter outer ring
d_2	162,2 mm	Raceway diameter of the inner ring
d_s	9,5 mm	Diameter lubrication hole
n_s	17,7 mm	Width of lubricating groove

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

e	0,33	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,06	Dynamic axial load factor
Y_2	3,06	Dynamic axial load factor
Y_0	2,01	Static axial load factor



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna