FAG

# 22326-E1A-XL-K-M-C4

Spherical Roller Bearing

Spherical roller bearing 223..-E1A-XL-K-M,
symmetric 2 outer ribs

X-life

## Informacje techniczne







### Twoja aktualna wersja produktu

| | | |
|---|---|---|
| Design | E1A | Without central rip |
| Bore type | K | Tapered, taper 1:12 |
| Cage | M | Brass Cage |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3 |
| Relubrication feature | Standard | |

### Main Dimensions & Performance Data

| | | |
|---|---|---|
| d | 130 mm | Bore diameter |
| D | 280 mm | Outside diameter |
| B | 93 mm | Width |
| $C_r$ | 1.250.000 N | Basic dynamic load rating, radial |
| $C_{0r}$ | 1.370.000 N | Basic static load rating, radial |
| $C_{ur}$ | 120.000 N | Fatigue load limit, radial |
| $n_G$ | 2.650 1/min | Limiting speed |
| $n_{\vartheta r}$ | 1.820 1/min | Reference speed |
| ≈m | 26,574 kg | Masa |

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

## Mounting dimensions

| | | |
|---|---|---|
| $d_{a\ min}$ | 147 mm | Minimum diameter shaft shoulder |
| $D_{a\ max}$ | 263 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$ | 3 mm | Maximum recess radius |
| $d_{a\ max}$ | 162 mm | Maximum diameter of shaft shoulder |
| $d_{b\ min}$ | 142 mm | Minimum cavity diameter of the sleeve |
| $B_{a\ min}$ | 8 mm | Minimum cavity width of the sleeve |

## Dimensions

| | | |
|---|---|---|
| $r_{min}$ | 4 mm | Minimum chamfer dimension |
| $D_1$ | 239,5 mm | Bore diameter outer ring |
| $d_2$ | 162,2 mm | Raceway diameter of the inner ring |
| $d_s$ | 9,5 mm | Diameter lubrication hole |
| $n_s$ | 17,7 mm | Width of lubricating groove |

## Temperature range

| | | |
|---|---|---|
| $T_{min}$ | -30 °C | Operating temperature min. |
| $T_{max}$ | 200 °C | Operating temperature max. |

## Calculation factors

| | | |
|---|---|---|
| e | 0,33 | Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 2,06 | Dynamic axial load factor |
| $Y_2$ | 3,06 | Dynamic axial load factor |
| $Y_0$ | 2,01 | Static axial load factor |

## Additional information

| | | |
|---|---|---|
| | H2326 | Adapter sleeve |
| | AHX2326G | Withdrawal sleeve |

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje