





FAG

22334-BE-XL-K 

Spherical Roller Bearing

Spherical roller bearings 223...-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	JPB	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	170 mm	Bore diameter
D	360 mm	Outside diameter
B	120 mm	Width
C _r	1.870.000 N	Basic dynamic load rating, radial
C _{0r}	2.220.000 N	Basic static load rating, radial
C _{ur}	178.000 N	Fatigue load limit, radial
n _G	2.130 1/min	Limiting speed
n _{gr}	1.320 1/min	Reference speed
≈m	56,9 kg	Masa



Mounting dimensions

d _{a min}	187 mm	Minimum diameter shaft shoulder
d _{a max}	204 mm	Maximum diameter of shaft shoulder
D _{a max}	343 mm	Maximum diameter of housing shoulder
r _{a max}	3 mm	Maximum recess radius
d _{b min}	185 mm	Minimum cavity diameter of the sleeve
B _{a min}	8 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	4 mm	Minimum chamfer dimension
D ₁	303,9 mm	Bore diameter outer ring
d ₂	213,1 mm	Raceway diameter of the inner ring
d _s	9,5 mm	Diameter lubrication hole
n _s	17,7 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,35	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	1,95	Dynamic axial load factor
Y ₂	2,9	Dynamic axial load factor
Y ₀	1,91	Static axial load factor

Additional information

H2334	Adapter sleeve
AH2334G	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna