





FAG


23026-E1-XL-K-TVPB-C3

Spherical Roller Bearing

Spherical roller bearings 230...-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	TVPB	Plastic cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	200 mm	Outside diameter
B	52 mm	Width
C _r	540.000 N	Basic dynamic load rating, radial
C _{0r}	730.000 N	Basic static load rating, radial
C _{ur}	71.000 N	Fatigue load limit, radial
n _G	3.600 1/min	Limiting speed
n _{gr}	2.600 1/min	Reference speed
≈m	5,392 kg	Masa



Mounting dimensions

d _{a min}	138,8 mm	Minimum diameter shaft shoulder
D _{a max}	191,2 mm	Maximum diameter of housing shoulder
r _{a max}	2 mm	Maximum recess radius
B _{a min}	8 mm	Minimum cavity width of the sleeve
d _{a max}	145 mm	Maximum diameter of shaft shoulder
d _{b min}	137 mm	Minimum cavity diameter of the sleeve

Dimensions

r _{min}	2 mm	Minimum chamfer dimension
D ₁	182,3 mm	Bore diameter outer ring
d ₂	145,9 mm	Raceway diameter of the inner ring
d _s	4,8 mm	Diameter lubrication hole
n _s	9,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

e	0,23	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,95	Dynamic axial load factor
Y ₂	4,4	Dynamic axial load factor
Y ₀	2,89	Static axial load factor

Additional information

H3026	Adapter sleeve
AHX3026	Withdrawal sleeve



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna