



FAG


23088-BEA-XL-MB1-H151

Spherical Roller Bearing

Spherical roller bearing 230...-BEA-XL-MB1, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BEA	With lose center lip ring
Bore type	Z	Cylindrical
Cage	MB1	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	Standard	
Locating feature, bearing outer ring	H151	1 Locking feature, bearing outer ring

Main Dimensions & Performance Data

d	440 mm	Bore diameter
D	650 mm	Outside diameter
B	157 mm	Width
C _r	3.950.000 N	Basic dynamic load rating, radial
C _{0r}	6.900.000 N	Basic static load rating, radial
C _{ur}	560.000 N	Fatigue load limit, radial
n _G	1.030 1/min	Limiting speed
n _{gr}	610 1/min	Reference speed
m	176 kg	Masa



Mounting dimensions

d _{a min}	463 mm	Minimum diameter shaft shoulder
D _{a max}	627 mm	
r _{a max}	5 mm	Maximum recess radius

Dimensions

r _{min}	6 mm	Minimum chamfer dimension
D ₁	589,3 mm	Bore diameter outer ring
d _s	12,5 mm	Diameter lubrication hole
n _s	23,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,21	
Y ₁	3,17	Dynamic axial load factor
Y ₂	4,72	Dynamic axial load factor
Y ₀	3,1	Static axial load factor



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna