



FAG



23152-BE-XL-K-T52BW-C3

Spherical Roller Bearing

Spherical roller bearings 231...-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	JPB	Sheet metal cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication	Standard	

Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	440 mm	Outside diameter
B	144 mm	Width
C _r	2.600.000 N	Basic dynamic load rating, radial
C _{0r}	3.900.000 N	Basic static load rating, radial
C _{ur}	310.000 N	Fatigue load limit, radial
n _G	1.500 1/min	Limiting speed
n _{gr}	860 1/min	Reference speed
m	84,78 kg	Masa



Mounting dimensions

$d_{a \min}$	277 mm	Minimum diameter shaft shoulder
$d_{a \max}$	302 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	423 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius
$d_{b \min}$	276 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	11 mm	Minimum cavity width of the sleeve

Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
D_1	382,7 mm	Bore diameter outer ring
d_2	301,7 mm	Raceway diameter of the inner ring
d_s	9,5 mm	Diameter lubrication hole
n_s	17,7 mm	Width of lubricating groove

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

e	0,32	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,12	Dynamic axial load factor
Y_2	3,15	Dynamic axial load factor
Y_0	2,07	Static axial load factor

Additional information

H3152X	Adapter sleeve
AH3152G	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna