



**FAG****23160-BEA-XL-MB1-H151B-C3**

Spherical Roller Bearing

Spherical roller bearing 231...-BEA-XL-MB1,
symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BEA	With lose center lip ring
Bore type	Z	Cylindrical
Cage	MB1	Solid brass cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication feature	Standard	
Locating feature, bearing outer ring	H151B	2 Locking features, bearing outer ring

Main Dimensions & Performance Data

d	300 mm	Bore diameter
D	500 mm	Outside diameter
B	160 mm	Width
C _r	3.250.000 N	Basic dynamic load rating, radial
C _{0r}	4.950.000 N	Basic static load rating, radial
C _{ur}	375.000 N	Fatigue load limit, radial
n _G	1.300 1/min	Limiting speed
n _{gr}	720 1/min	Reference speed
m	125,115 kg	Masa



Mounting dimensions

$d_{a\ min}$	320 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	480 mm	
$r_{a\ max}$	4 mm	Maximum recess radius

Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
D_1	436,8 mm	Bore diameter outer ring
d_s	9,5 mm	Diameter lubrication hole
n_s	17,7 mm	Width of lubricating groove

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

e	0,31	
Y_1	2,18	Dynamic axial load factor
Y_2	3,24	Dynamic axial load factor
Y_0	2,13	Static axial load factor



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna