



FAG



23192-BEA-XL-K-MB1-C3

Spherical Roller Bearing

Spherical roller bearing 231...-BEA-XL-K-MB1, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | BEA          | With lose center lip ring         |
| Bore type                 | K            | Tapered, taper 1:12               |
| Cage                      | MB1          | Solid brass cage                  |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication feature     | Standard     |                                   |

Main Dimensions & Performance Data

|                 |              |                                   |
|-----------------|--------------|-----------------------------------|
| d               | 460 mm       | Bore diameter                     |
| D               | 760 mm       | Outside diameter                  |
| B               | 240 mm       | Width                             |
| C <sub>r</sub>  | 6.900.000 N  | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 11.500.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 760.000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 770 1/min    | Limiting speed                    |
| n <sub>gr</sub> | 395 1/min    | Reference speed                   |
| m               | 420 kg       | Masa                              |



Mounting dimensions

|                    |        |                                       |
|--------------------|--------|---------------------------------------|
| d <sub>a min</sub> | 492 mm | Minimum diameter shaft shoulder       |
| D <sub>a max</sub> | 728 mm |                                       |
| r <sub>a max</sub> | 6 mm   | Maximum recess radius                 |
| d <sub>a max</sub> | 533 mm |                                       |
| d <sub>b min</sub> | 484 mm | Minimum cavity diameter of the sleeve |
| B <sub>a min</sub> | 17 mm  | Minimum cavity width of the sleeve    |

Dimensions

|                  |          |                             |
|------------------|----------|-----------------------------|
| r <sub>min</sub> | 7,5 mm   | Minimum chamfer dimension   |
| D <sub>1</sub>   | 663,4 mm | Bore diameter outer ring    |
| d <sub>s</sub>   | 12,5 mm  | Diameter lubrication hole   |
| n <sub>s</sub>   | 23,5 mm  | Width of lubricating groove |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Calculation factors

|                |      |                           |
|----------------|------|---------------------------|
| e              | 0,31 |                           |
| Y <sub>1</sub> | 2,21 | Dynamic axial load factor |
| Y <sub>2</sub> | 3,29 | Dynamic axial load factor |
| Y <sub>0</sub> | 2,16 | Static axial load factor  |

Additional information

|            |                   |
|------------|-------------------|
| H3192-HG   | Adapter sleeve    |
| AHX3192G-H | Withdrawal sleeve |



## Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna