



FAG

23218-E1A-XL-K-M-C3

Spherical Roller Bearing

Spherical roller bearings 232...-E1A-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | E1A          | Without central rip               |
| Bore type                 | K            | Tapered, taper 1:12               |
| Cage                      | M            | Brass Cage                        |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication feature     | Standard     |                                   |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 90 mm       | Bore diameter                     |
| D               | 160 mm      | Outside diameter                  |
| B               | 52,4 mm     | Width                             |
| C <sub>r</sub>  | 445.000 N   | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 520.000 N   | Basic static load rating, radial  |
| C <sub>ur</sub> | 50.000 N    | Fatigue load limit, radial        |
| n <sub>G</sub>  | 4.250 1/min | Limiting speed                    |
| n <sub>gr</sub> | 2.650 1/min | Reference speed                   |
| ≈m              | 4,329 kg    | Masa                              |



Mounting dimensions

|                    |        |                                       |
|--------------------|--------|---------------------------------------|
| d <sub>a min</sub> | 101 mm | Minimum diameter shaft shoulder       |
| D <sub>a max</sub> | 149 mm | Maximum diameter of housing shoulder  |
| r <sub>a max</sub> | 2 mm   | Maximum recess radius                 |
| d <sub>a max</sub> | 107 mm | Maximum diameter of shaft shoulder    |
| d <sub>b min</sub> | 100 mm | Minimum cavity diameter of the sleeve |
| B <sub>a min</sub> | 18 mm  | Minimum cavity width of the sleeve    |

Dimensions

|                  |        |                             |
|------------------|--------|-----------------------------|
| r <sub>min</sub> | 2 mm   | Minimum chamfer dimension   |
| D <sub>1</sub>   | 140 mm | Bore diameter outer ring    |
| d <sub>s</sub>   | 3,2 mm | Diameter lubrication hole   |
| n <sub>s</sub>   | 6,5 mm | Width of lubricating groove |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Calculation factors

|                |      |                                                                                  |
|----------------|------|----------------------------------------------------------------------------------|
| e              | 0,31 | Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y |
| Y <sub>1</sub> | 2,2  | Dynamic axial load factor                                                        |
| Y <sub>2</sub> | 3,27 | Dynamic axial load factor                                                        |
| Y <sub>0</sub> | 2,15 | Static axial load factor                                                         |

Additional information

|         |                   |
|---------|-------------------|
| H2318   | Adapter sleeve    |
| AHX3218 | Withdrawal sleeve |



### Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna