

FAG



23224-E1-XL-K-TVPB

Spherical Roller Bearing

Spherical roller bearings 232...-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	TVPB	Plastic cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	120 mm	Bore diameter
D	215 mm	Outside diameter
B	76 mm	Width
C _r	820.000 N	Basic dynamic load rating, radial
C _{0r}	1.020.000 N	Basic static load rating, radial
C _{ur}	82.000 N	Fatigue load limit, radial
n _G	3.000 1/min	Limiting speed
n _{gr}	1.910 1/min	Reference speed
≈m	10,913 kg	Masa



Mounting dimensions

d a min	132 mm	Minimum diameter shaft shoulder
D a max	203 mm	Maximum diameter of housing shoulder
r a max	2,1 mm	Maximum recess radius
B a min	17 mm	Minimum cavity width of the sleeve
d a max	139 mm	Maximum diameter of shaft shoulder
d b min	131 mm	Minimum cavity diameter of the sleeve

Dimensions

r min	2,1 mm	Minimum chamfer dimension
D 1	185,5 mm	Bore diameter outer ring
d 2	139 mm	Raceway diameter of the inner ring
d s	4,8 mm	Diameter lubrication hole
n s	9,5 mm	Width of lubricating groove

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Calculation factors

e	0,33	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y 1	2,03	Dynamic axial load factor
Y 2	3,02	Dynamic axial load factor
Y 0	1,98	Static axial load factor

Additional information

H2324	Adapter sleeve
AHX3224A	Withdrawal sleeve



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna