



FAG

23224-E1A-XL-K-M-C3

Spherical Roller Bearing

Spherical roller bearings 232...-E1A-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	120 mm	Bore diameter
D	215 mm	Outside diameter
B	76 mm	Width
C _r	820.000 N	Basic dynamic load rating, radial
C _{0r}	1.020.000 N	Basic static load rating, radial
C _{ur}	82.000 N	Fatigue load limit, radial
n _G	3.000 1/min	Limiting speed
n _{gr}	1.910 1/min	Reference speed

≈m	11,436 kg	Masa
----	-----------	------



Mounting dimensions

d _{a min}	132 mm	Minimum diameter shaft shoulder
D _{a max}	203 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum recess radius
d _{a max}	141 mm	Maximum diameter of shaft shoulder
d _{b min}	131 mm	Minimum cavity diameter of the sleeve
B _{a min}	17 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
D ₁	185,5 mm	Bore diameter outer ring
d _s	4,8 mm	Diameter lubrication hole
n _s	9,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,33	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,03	Dynamic axial load factor
Y ₂	3,02	Dynamic axial load factor
Y ₀	1,98	Static axial load factor

Additional information

H2324	Adapter sleeve
AHX3224A	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna