


FAG

23226-E1-XL-TVPB-C3

Spherical Roller Bearing

Spherical roller bearings 232...-E1, main dimensions to DIN 635-2

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1	Without central rip
Bore type	Z	Cylindrical
Cage	TVPB	Plastic cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	230 mm	Outside diameter
B	80 mm	Width
C _r	910.000 N	Basic dynamic load rating, radial
C _{0r}	1.150.000 N	Basic static load rating, radial
C _{ur}	91.000 N	Fatigue load limit, radial
n _G	2.850 1/min	Limiting speed
n _{gr}	1.740 1/min	Reference speed
≈m	13,28 kg	Masa



Mounting dimensions

d _{a min}	144 mm	Minimum diameter shaft shoulder
D _{a max}	216 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum recess radius

Dimensions

r _{min}	3 mm	Minimum chamfer dimension
D ₁	199,3 mm	Bore diameter outer ring
d ₂	150 mm	Raceway diameter of the inner ring
d _s	4,8 mm	Diameter lubrication hole
n _s	9,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

e	0,33	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,07	Dynamic axial load factor
Y ₂	3,09	Dynamic axial load factor
Y ₀	2,03	Static axial load factor



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna