



FAG

23234-E1A-XL-M-C4

Spherical Roller Bearing

Spherical roller bearings 232...-E1A, main dimensions to DIN 635-2

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1A	Without central rip
Bore type	Z	Cylindrical
Cage	M	Brass Cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	170 mm	Bore diameter
D	310 mm	Outside diameter
B	110 mm	Width
C _r	1.640.000 N	Basic dynamic load rating, radial
C _{0r}	2.170.000 N	Basic static load rating, radial
C _{ur}	168.000 N	Fatigue load limit, radial
n _G	2.090 1/min	Limiting speed
n _{gr}	1.160 1/min	Reference speed
≈m	36,04 kg	Masa

Mounting dimensions

d _{a min}	187 mm	Minimum diameter shaft shoulder
D _{a max}	293 mm	Maximum diameter of housing shoulder
r _{a max}	3 mm	Maximum recess radius



Dimensions

r _{min}	4 mm	Minimum chamfer dimension
D ₁	267,4 mm	Bore diameter outer ring
d _s	8 mm	Diameter lubrication hole
n _s	15 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,33	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,03	Dynamic axial load factor
Y ₂	3,02	Dynamic axial load factor
Y ₀	1,98	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna
	Nieosiowość dynamiczna