

FAG



23236-E1A-XL-K-M

Spherical Roller Bearing

Spherical roller bearings 232...-E1A-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	180 mm	Bore diameter
D	320 mm	Outside diameter
B	112 mm	Width
C _r	1.720.000 N	Basic dynamic load rating, radial
C _{0r}	2.340.000 N	Basic static load rating, radial
C _{ur}	178.000 N	Fatigue load limit, radial
n _G	2.010 1/min	Limiting speed
n _{gr}	1.090 1/min	Reference speed
≈m	37,279 kg	Masa



Mounting dimensions

d _{a min}	197 mm	Minimum diameter shaft shoulder
D _{a max}	303 mm	Maximum diameter of housing shoulder
r _{a max}	3 mm	Maximum recess radius
d _{a max}	210 mm	Maximum diameter of shaft shoulder
d _{b min}	195 mm	Minimum cavity diameter of the sleeve
B _{a min}	22 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	4 mm	Minimum chamfer dimension
D ₁	277,3 mm	Bore diameter outer ring
d _s	8 mm	Diameter lubrication hole
n _s	15 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,33	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,07	Dynamic axial load factor
Y ₂	3,09	Dynamic axial load factor
Y ₀	2,03	Static axial load factor

Additional information

H2336	Adapter sleeve
AH3236G	Withdrawal sleeve



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Łożysko gabarytowe



Nieosiowość statyczna



Nieosiowość dynamiczna