



FAG

23240-BE-XL-C4

Spherical Roller Bearing

Spherical roller bearing 232...-BE-XL,
symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	200 mm	Bore diameter
D	360 mm	Outside diameter
B	128 mm	Width
C _r	1.940.000 N	Basic dynamic load rating, radial
C _{0r}	2.700.000 N	Basic static load rating, radial
C _{ur}	226.000 N	Fatigue load limit, radial
n _G	1.870 1/min	Limiting speed
n _{gr}	1.000 1/min	Reference speed
≈m	55,63 kg	Masa

Mounting dimensions

d _{a min}	217 mm	Minimum diameter shaft shoulder
D _{a max}	343 mm	Maximum diameter of housing shoulder
r _{a max}	3 mm	Maximum recess radius



Dimensions

r _{min}	4 mm	Minimum chamfer dimension
D ₁	305,3 mm	Bore diameter outer ring
d ₂	235 mm	Raceway diameter of the inner ring
d _s	9,5 mm	Diameter lubrication hole
n _s	17,7 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,35	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	1,95	Dynamic axial load factor
Y ₂	2,9	Dynamic axial load factor
Y ₀	1,91	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe
	Nieosiowość statyczna
	Nieosiowość dynamiczna