



FAG

23256-BEA-XL-K-MB1-H40

Spherical Roller Bearing

Spherical roller bearing 232...-BEA-XL-K-MB1-H40, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BEA	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	MB1	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	H40	Without lubricating groove and holes

Main Dimensions & Performance Data

d	280 mm	Bore diameter
D	500 mm	Outside diameter
B	176 mm	Width
C _r	3.550.000 N	Basic dynamic load rating, radial
C _{0r}	5.200.000 N	Basic static load rating, radial
C _{ur}	395.000 N	Fatigue load limit, radial
n _G	1.280 1/min	Limiting speed
n _{gr}	630 1/min	Reference speed
≈m	144,385 kg	Masa



Mounting dimensions

$d_{a \min}$	300 mm	Minimum diameter shaft shoulder
$D_{a \max}$	480 mm	
$r_{a \max}$	4 mm	Maximum recess radius
$d_{a \max}$	329 mm	
$d_{b \min}$	299 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	11 mm	Minimum cavity width of the sleeve

Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
D_1	425,4 mm	Bore diameter outer ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

e	0,34	
Y_1	1,96	Dynamic axial load factor
Y_2	2,92	Dynamic axial load factor
Y_0	1,92	Static axial load factor

Additional information

H2356X	Adapter sleeve
AH2356G	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna