



FAG



23264-BEA-XL-K-MB1-C4

Spherical Roller Bearing

Spherical roller bearing 232...-BEA-XL-K-MB1, symmetric 2 outer ribs with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BEA	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	MB1	Solid brass cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	320 mm	Bore diameter
D	580 mm	Outside diameter
B	208 mm	Width
C _r	4.650.000 N	Basic dynamic load rating, radial
C _{0r}	7.000.000 N	Basic static load rating, radial
C _{ur}	510.000 N	Fatigue load limit, radial
n _G	1.060 1/min	Limiting speed
n _{gr}	510 1/min	Reference speed
≈m	230,5 kg	Masa



Mounting dimensions

d _{a min}	340 mm	Minimum diameter shaft shoulder
D _{a max}	560 mm	
r _{a max}	4 mm	Maximum recess radius
d _{a max}	378 mm	
d _{b min}	343 mm	Minimum cavity diameter of the sleeve
B _{a min}	13 mm	Minimum cavity width of the sleeve

Dimensions

r _{min}	5 mm	Minimum chamfer dimension
D ₁	490,4 mm	Bore diameter outer ring
d _s	12,5 mm	Diameter lubrication hole
n _s	23,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,35	
Y ₁	1,91	Dynamic axial load factor
Y ₂	2,85	Dynamic axial load factor
Y ₀	1,87	Static axial load factor

Additional information

H3264-HG	Adapter sleeve
AH3264G-H	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna