



FAG

234407-M-SP

Axial angular contact ball bearing

Axial angular contact ball bearings 2344, double direction, separable, restricted tolerances

Informacje techniczne



Twoja aktualna wersja produktu

Cage	M	Brass Cage
Tolerance class	SP	Tolerance class SP

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	62 mm	Outside diameter
B	34 mm	Width
C	17 mm	Width, outer ring
C _a	19.100 N	Basic dynamic load rating, axial
C _{0a}	46.500 N	Basic static load rating, axial
C _{ua}	4.300 N	Fatigue load limit, axial
n _{G Grease}	9.500 1/min	Limiting speed for grease lubrication
n _{G Oil}	1.400 1/min	Limiting speed for oil lubrication
≈m	381 g	Masa



Mounting dimensions

d _a	46,5 mm	Diameter shaft shoulder
d _a	h12	Diameter shaft shoulder clearance
D _a	57 mm	Shoulder diameter outer ring
D _a	H12	Shoulder diameter outer ring clearance
r _{a max}	1 mm	Maximum recess radius
r _{a1 max}	0,15 mm	Maximum recess radius
α	60 °	Contact angle
a	103 mm	Distance between the apexes of the pressure cones

Dimensions

d ₁	53 mm	Rip diameter shaft washer
B ₁	8,5 mm	Height wave disc
r _{min}	1 mm	Minimum chamfer dimension
r _{1 min}	0,15 mm	Minimum chamfer dimension
d _s	3,2 mm	Diameter lubrication hole
n _s	4,8 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Additional information

c _a	316 N/μm	Axial rigidity
K _{aE}	382 N	Lift-off force
F _v	134 N	Preload force



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia