





FAG

23956-K-MB

Spherical Roller Bearing

Spherical roller bearing 239...-K-MB,
symmetric 3 ribs

Informacje techniczne



Twoja aktualna wersja produktu

Bore type	K	Tapered, taper 1:12
Cage	MB	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	280 mm	Bore diameter
D	380 mm	Outside diameter
B	75 mm	Width
C _r	970.000 N	Basic dynamic load rating, radial
C _{0r}	2.040.000 N	Basic static load rating, radial
C _{ur}	133.000 N	Fatigue load limit, radial
n _G	2.000 1/min	Limiting speed
n _{gr}	1.100 1/min	Reference speed
m	23,955 kg	Masa

Mounting dimensions

d _{a min}	290,2 mm	Minimum diameter shaft shoulder
D _{a max}	369,8 mm	Maximum diameter of housing shoulder
r _{a max}	2,1 mm	Maximum recess radius
d _{a max}	303 mm	Maximum diameter of shaft shoulder
d _{b min}	290 mm	Minimum cavity diameter of the sleeve
B _{a min}	12 mm	Minimum cavity width of the sleeve



Dimensions

r _{min}	2,1 mm	Minimum chamfer dimension
D ₁	350 mm	Bore diameter outer ring
d _s	8 mm	Diameter lubrication hole
n _s	15 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,18	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	3,76	Dynamic axial load factor
Y ₂	5,59	Dynamic axial load factor
Y ₀	3,67	Static axial load factor

Additional information

H3956	Adapter sleeve
AH3956G	Withdrawal sleeve



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna