



FAG

23968-MB-H40AB-C3

Spherical Roller Bearing

Spherical roller bearing 239...-MB-H40AB,  
symmetric 3 ribs

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                       |
|---------------------------|--------------|---------------------------------------|
| Bore type                 | Z            | Cylindrical                           |
| Cage                      | MB           | Solid brass cage                      |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN     |
| Relubrication feature     | H40AB        | 6 lubricating holes at the inner ring |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 340 mm      | Bore diameter                     |
| D               | 460 mm      | Outside diameter                  |
| B               | 90 mm       | Width                             |
| C <sub>r</sub>  | 1.370.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 3.000.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 204.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 1.610 1/min | Limiting speed                    |
| n <sub>gr</sub> | 860 1/min   | Reference speed                   |
| ≈m              | 43,4 kg     | Masa                              |

Mounting dimensions

|                    |          |                                      |
|--------------------|----------|--------------------------------------|
| d <sub>a min</sub> | 352,4 mm | Minimum diameter shaft shoulder      |
| D <sub>a max</sub> | 447,6 mm | Maximum diameter of housing shoulder |
| r <sub>a max</sub> | 2,5 mm   | Maximum recess radius                |



Dimensions

|                  |          |                             |
|------------------|----------|-----------------------------|
| r <sub>min</sub> | 3 mm     | Minimum chamfer dimension   |
| D <sub>1</sub>   | 426,7 mm | Bore diameter outer ring    |
| d <sub>s</sub>   | 9,5 mm   | Diameter lubrication hole   |
| n <sub>s</sub>   | 17,7 mm  | Width of lubricating groove |

Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -30 °C | Operating temperature min. |
| T <sub>max</sub> | 200 °C | Operating temperature max. |

Calculation factors

|                |      |                                                                                  |
|----------------|------|----------------------------------------------------------------------------------|
| e              | 0,18 | Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y |
| Y <sub>1</sub> | 3,85 | Dynamic axial load factor                                                        |
| Y <sub>2</sub> | 5,73 | Dynamic axial load factor                                                        |
| Y <sub>0</sub> | 3,76 | Static axial load factor                                                         |

Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Obciążenie osiowe dwukierunkowe   |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |
|  | Nieosiowość statyczna             |
|  | Nieosiowość dynamiczna            |