



FAG

23992-B-MB-C3

Spherical Roller Bearing

Spherical roller bearing 239...-B-MB,  
symmetric 3 ribs

Informacje techniczne



Twoja aktualna wersja produktu

|                           |              |                                   |
|---------------------------|--------------|-----------------------------------|
| Design                    | B            | With fixed central rib            |
| Bore type                 | Z            | Cylindrical                       |
| Cage                      | MB           | Solid brass cage                  |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN |
| Relubrication feature     | Standard     |                                   |

Main Dimensions & Performance Data

|                 |             |                                   |
|-----------------|-------------|-----------------------------------|
| d               | 460 mm      | Bore diameter                     |
| D               | 620 mm      | Outside diameter                  |
| B               | 118 mm      | Width                             |
| C <sub>r</sub>  | 2.270.000 N | Basic dynamic load rating, radial |
| C <sub>0r</sub> | 5.400.000 N | Basic static load rating, radial  |
| C <sub>ur</sub> | 380.000 N   | Fatigue load limit, radial        |
| n <sub>G</sub>  | 1.080 1/min | Limiting speed                    |
| n <sub>gr</sub> | 590 1/min   | Reference speed                   |
| m               | 103,5 kg    | Masa                              |

Mounting dimensions

|                    |          |                                      |
|--------------------|----------|--------------------------------------|
| d <sub>a min</sub> | 474,6 mm | Minimum diameter shaft shoulder      |
| D <sub>a max</sub> | 605,4 mm | Maximum diameter of housing shoulder |
| r <sub>a max</sub> | 3 mm     | Maximum recess radius                |



Dimensions

|           |          |                             |
|-----------|----------|-----------------------------|
| $r_{min}$ | 4 mm     | Minimum chamfer dimension   |
| $D_1$     | 573,3 mm | Bore diameter outer ring    |
| $d_s$     | 12,5 mm  | Diameter lubrication hole   |
| $n_s$     | 23,5 mm  | Width of lubricating groove |

Temperature range

|           |        |                            |
|-----------|--------|----------------------------|
| $T_{min}$ | -30 °C | Operating temperature min. |
| $T_{max}$ | 200 °C | Operating temperature max. |

Calculation factors

|       |      |                                                                                      |
|-------|------|--------------------------------------------------------------------------------------|
| $e$   | 0,18 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 3,85 | Dynamic axial load factor                                                            |
| $Y_2$ | 5,73 | Dynamic axial load factor                                                            |
| $Y_0$ | 3,76 | Static axial load factor                                                             |

Właściwości

|                                                                                     |                                   |
|-------------------------------------------------------------------------------------|-----------------------------------|
|  | Obciążenie promieniowe            |
|  | Obciążenie osiowe jednokierunkowe |
|  | Obciążenie osiowe dwukierunkowe   |
|  | Smarowanie smarem                 |
|  | Smarowanie olejem                 |
|  | Bez uszczelnienia                 |
|  | Łożysko gabarytowe                |
|  | Nieosiowość statyczna             |
|  | Nieosiowość dynamiczna            |