

FAG



24128-BE-XL-C4

Spherical Roller Bearing

Spherical roller bearing 241...-BE-XL,
symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	140 mm	Bore diameter
D	225 mm	Outside diameter
B	85 mm	Width
C _r	800.000 N	Basic dynamic load rating, radial
C _{0r}	1.190.000 N	Basic static load rating, radial
C _{ur}	127.000 N	Fatigue load limit, radial
n _G	2.650 1/min	Limiting speed
n _{gr}	1.430 1/min	Reference speed
≈m	12,775 kg	Masa



Mounting dimensions

$d_{a\ min}$	152 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	213 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	2,1 mm	Maximum recess radius

Dimensions

$r_{\ min}$	2,1 mm	Minimum chamfer dimension
D_1	194,4 mm	Bore diameter outer ring
d_2	158,9 mm	Raceway diameter of the inner ring
d_s	4,8 mm	Diameter lubrication hole
n_s	9,5 mm	Width of lubricating groove

Temperature range

$T_{\ min}$	-30 °C	Operating temperature min.
$T_{\ max}$	200 °C	Operating temperature max.

Calculation factors

e	0,34	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	1,99	Dynamic axial load factor
Y_2	2,96	Dynamic axial load factor
Y_0	1,94	Static axial load factor



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna