

FAG



24130-BE-XL

Spherical Roller Bearing

Spherical roller bearing 241...-BE-XL,
symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	250 mm	Outside diameter
B	100 mm	Width
C _r	1.050.000 N	Basic dynamic load rating, radial
C _{0r}	1.520.000 N	Basic static load rating, radial
C _{ur}	153.000 N	Fatigue load limit, radial
n _G	2.370 1/min	Limiting speed
n _{gr}	1.270 1/min	Reference speed
≈m	19,6 kg	Masa



Mounting dimensions

$d_{a \min}$	162 mm	Minimum diameter shaft shoulder
$D_{a \max}$	238 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius

Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
D_1	213 mm	Bore diameter outer ring
d_2	170,3 mm	Raceway diameter of the inner ring
d_s	4,8 mm	Diameter lubrication hole
n_s	9,5 mm	Width of lubricating groove

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

Calculation factors

e	0,37	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	1,83	Dynamic axial load factor
Y_2	2,72	Dynamic axial load factor
Y_0	1,79	Static axial load factor



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Obciążenie osiowe dwukierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Nieosiowość statyczna



Nieosiowość dynamiczna