



FAG

24140-BE-XL

Spherical Roller Bearing

Spherical roller bearing 241...-BE-XL, symmetric with rib washer

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	200 mm	Bore diameter
D	340 mm	Outside diameter
B	140 mm	Width
C _r	1.880.000 N	Basic dynamic load rating, radial
C _{0r}	2.800.000 N	Basic static load rating, radial
C _{ur}	260.000 N	Fatigue load limit, radial
n _G	1.780 1/min	Limiting speed
n _{gr}	840 1/min	Reference speed
≈m	51,2 kg	Masa



Mounting dimensions

d _{a min}	214 mm	Minimum diameter shaft shoulder
D _{a max}	326 mm	Maximum diameter of housing shoulder
r _{a max}	2,5 mm	Maximum recess radius

Dimensions

r _{min}	3 mm	Minimum chamfer dimension
D ₁	287,9 mm	Bore diameter outer ring
d ₂	227,1 mm	Raceway diameter of the inner ring
d _s	6,3 mm	Diameter lubrication hole
n _s	12,2 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,39	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	1,71	Dynamic axial load factor
Y ₂	2,54	Dynamic axial load factor
Y ₀	1,67	Static axial load factor



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna