FAG

24148-BE-XL-C4

Spherical Roller Bearing

Spherical roller bearing 241..-BE-XL,
symmetric with rib washer

X-life

Informacje techniczne





Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	400 mm	Outside diameter
B	160 mm	Width
C_r	2.600.000 N	Basic dynamic load rating, radial
C_{0r}	3.900.000 N	Basic static load rating, radial
C_{ur}	340.000 N	Fatigue load limit, radial
n_G	1.470 1/min	Limiting speed
$n_{\vartheta r}$	650 1/min	Reference speed
≈m	78,55 kg	Masa

Mounting dimensions

$d_{a\ min}$	257 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	383 mm	Maximum diameter of housing shoulder
$r_{a\ max}$	3 mm	Maximum recess radius

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

Dimensions

r_{min}	4 mm	Minimum chamfer dimension
D_1	339 mm	Bore diameter outer ring
d_2	267,3 mm	Raceway diameter of the inner ring
d_s	6,3 mm	Diameter lubrication hole
n_s	12,2 mm	Width of lubricating groove

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Calculation factors

e	0,39	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y_1	1,71	Dynamic axial load factor
Y_2	2,54	Dynamic axial load factor
Y_0	1,67	Static axial load factor

Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Obciążenie osiowe dwukierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia
- Łożysko gabarytowe
- Nieosiowość statyczna
- Nieosiowość dynamiczna

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje