



FAG

24156-BE-XL

Spherical Roller Bearing

Spherical roller bearing 241...-BE-XL,
symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	280 mm	Bore diameter
D	460 mm	Outside diameter
B	180 mm	Width
C _r	3.300.000 N	Basic dynamic load rating, radial
C _{0r}	5.200.000 N	Basic static load rating, radial
C _{ur}	435.000 N	Fatigue load limit, radial
n _G	1.230 1/min	Limiting speed
n _{gr}	520 1/min	Reference speed

Mounting dimensions

d _{a min}	300 mm	Minimum diameter shaft shoulder
D _{a max}	440 mm	Maximum diameter of housing shoulder
r _{a max}	4 mm	Maximum recess radius



Dimensions

r _{min}	5 mm	Minimum chamfer dimension
D ₁	392,4 mm	Bore diameter outer ring
d ₂	312,8 mm	Raceway diameter of the inner ring
d _s	8 mm	Diameter lubrication hole
n _s	15 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,38	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	1,76	Dynamic axial load factor
Y ₂	2,62	Dynamic axial load factor
Y ₀	1,72	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe
	Nieosiowość statyczna
	Nieosiowość dynamiczna