



FAG



24160-BE-XL-C5

Spherical Roller Bearing

Spherical roller bearing 241...-BE-XL,
symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	C5 (Group 5)	Internal clearance larger than C4
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	300 mm	Bore diameter
D	500 mm	Outside diameter
B	200 mm	Width
C _r	3.950.000 N	Basic dynamic load rating, radial
C _{0r}	6.400.000 N	Basic static load rating, radial
C _{ur}	500.000 N	Fatigue load limit, radial
n _G	1.100 1/min	Limiting speed
n _{gr}	450 1/min	Reference speed
≈m	155,45 kg	Masa

Mounting dimensions

d _{a min}	320 mm	Minimum diameter shaft shoulder
D _{a max}	480 mm	Maximum diameter of housing shoulder
r _{a max}	4 mm	Maximum recess radius



Dimensions

r_{min}	5 mm	Minimum chamfer dimension
D_1	422,8 mm	Bore diameter outer ring
d_2	338,2 mm	Raceway diameter of the inner ring
d_s	8 mm	Diameter lubrication hole
n_s	15 mm	Width of lubricating groove

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Calculation factors

e	0,39	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	1,72	Dynamic axial load factor
Y_2	2,56	Dynamic axial load factor
Y_0	1,68	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe
	Nieosiowość statyczna
	Nieosiowość dynamiczna