



FAG



24164-BE-XL-H40

Spherical Roller Bearing

Spherical roller bearing 241...-BE-XL-H40,
symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	H40	Without lubricating groove and holes

Main Dimensions & Performance Data

d	320 mm	Bore diameter
D	540 mm	Outside diameter
B	218 mm	Width
C _r	4.600.000 N	Basic dynamic load rating, radial
C _{0r}	7.300.000 N	Basic static load rating, radial
C _{ur}	570.000 N	Fatigue load limit, radial
n _G	1.010 1/min	Limiting speed
n _{gr}	415 1/min	Reference speed
≈m	200 kg	Masa

Mounting dimensions

d _{a min}	340 mm	Minimum diameter shaft shoulder
D _{a max}	520 mm	Maximum diameter of housing shoulder
r _{a max}	4 mm	Maximum recess radius



Dimensions

r _{min}	5 mm	Minimum chamfer dimension
D ₁	455,5 mm	Bore diameter outer ring
d ₂	359 mm	Raceway diameter of the inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,4	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	1,69	Dynamic axial load factor
Y ₂	2,52	Dynamic axial load factor
Y ₀	1,65	Static axial load factor

Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Obciążenie osiowe dwukierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Nieosiowość statyczna
-  Nieosiowość dynamiczna