



FAG


24184-BE-XL

Spherical Roller Bearing

Spherical roller bearing 241...-BE-XL,
symmetric with rib washer

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Design	BE	With lose center lip ring
Bore type	Z	Cylindrical
Cage	JPB	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication feature	Standard	

Main Dimensions & Performance Data

d	420 mm	Bore diameter
D	700 mm	Outside diameter
B	280 mm	Width
C _r	7.400.000 N	Basic dynamic load rating, radial
C _{0r}	12.600.000 N	Basic static load rating, radial
C _{ur}	890.000 N	Fatigue load limit, radial
n _G	720 1/min	Limiting speed
n _{gr}	270 1/min	Reference speed
≈m	436 kg	Masa

Mounting dimensions

d _{a min}	446 mm	Minimum diameter shaft shoulder
D _{a max}	674 mm	Maximum diameter of housing shoulder
r _{a max}	5 mm	Maximum recess radius



Dimensions

r _{min}	6 mm	Minimum chamfer dimension
D ₁	592,2 mm	Bore diameter outer ring
d ₂	472,7 mm	Raceway diameter of the inner ring
d _s	12,5 mm	Diameter lubrication hole
n _s	23,5 mm	Width of lubricating groove

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.

Calculation factors

e	0,39	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	1,72	Dynamic axial load factor
Y ₂	2,56	Dynamic axial load factor
Y ₀	1,68	Static axial load factor

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Łożysko gabarytowe
	Nieosiowość statyczna
	Nieosiowość dynamiczna