


**FAG****29230-E1-MB**

Axial spherical roller bearing

Axial spherical roller bearing 292...-E1-MB,
with flanging ring

Informacje techniczne



Twoja aktualna wersja produktu

Heat treatment	Standard	Standard
Cage	MB	Solid brass cage
Locating feature, housing washer	Without	
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	215 mm	Outside diameter
T	39 mm	Section height
C _a	425.000 N	Basic dynamic load rating, axial
C _{0a}	1.720.000 N	Basic static load rating, axial
C _{ua}	207.000 N	Fatigue load limit, axial
n _G	3.150 1/min	Limiting speed
n _{gr}	1.540 1/min	Reference speed
≈m	4,485 kg	Masa



Mounting dimensions

$d_{a\ min}$	185 mm	Minimum diameter shaft shoulder
$D_{a\ max}$	193 mm	Maximum diameter of housing shoulder
$D_{b\ min}$	219 mm	Minimum bore diameter housing
$d_{b\ max}$	157 mm	Maximum distance sleeve
$r_{a\ max}$	1,5 mm	Maximum recess radius

Dimensions

D_1	176 mm	Bore diameter housing washer
d_1	200 mm	Rip diameter shaft washer
r_{min}	1,5 mm	Minimum chamfer dimension
T_1	20,5 mm	Height of the housing washer
T_2	14 mm	Height of shaft washer
T_3	25 mm	Height of the shaft washer
T_4	37 mm	Height of shaft washer, inc. lip ring
A	82 mm	Distance of the center point

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Smarowanie smarem
	Smarowanie olejem
	Bez uszczelnienia
	Nieosiowość statyczna
	Nieosiowość dynamiczna