



FAG

29436-E1-XL

Axial spherical roller bearing

Axial spherical roller bearing 294..-E1-XL, no flanging ring

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Heat treatment	Standard	Standard
Locating feature, housing washer	Without	
Cage	JP	Sheet metal cage
Handling thread holes	Without	
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	180 mm	Bore diameter
D	360 mm	Outside diameter
T	109 mm	Height
C _a	2.850.000 N	Basic dynamic load rating, axial
C _{0a}	7.700.000 N	Basic static load rating, axial
C _{ua}	770.000 N	Fatigue load limit, axial
n _G	1.860 1/min	Limiting speed
n _{gr}	940 1/min	Reference speed
≈m	45,2 kg	Masa



Mounting dimensions

d _a min	265 mm	Minimum diameter shaft shoulder
D _a max	305 mm	Maximum diameter of housing shoulder
D _b min	366 mm	Minimum bore diameter housing
d _b max	210 mm	Maximum distance sleeve
d _{b1} max	197 mm	Maximum chamfer diameter of distance sleeve
r _a max	4 mm	Maximum recess radius
	30 °	Angle of chamfer of the distance sleeve

Dimensions

D ₁	250 mm	Bore diameter housing washer
d ₁	315,5 mm	Rip diameter shaft washer
r _{min}	5 mm	Minimum chamfer dimension
T ₁	53 mm	Height of the housing washer
T ₃	69,5 mm	Height of the shaft washer
T ₅	96 mm	Distance shaft washer - cage
A	110 mm	Distance of the center point

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



Łożysko gabarytowe



Nieosiowość statyczna



Nieosiowość dynamiczna