



FAG

29460-E1-XL-THI

Axial spherical roller bearing

Axial spherical roller bearing 294...E1-XL, no flanging ring



X-life




Informacje techniczne

Twoja aktualna wersja produktu

Heat treatment	Standard	Standard
Locating feature, housing washer	Without	
Cage	JP	Sheet metal cage
Handling thread holes	THI	Handling thread holes, shaft washer
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	300 mm	Bore diameter
D	540 mm	Outside diameter
T	145 mm	Height
C _a	5.200.000 N	Basic dynamic load rating, axial
C _{0a}	16.200.000 N	Basic static load rating, axial
C _{ua}	1.550.000 N	Fatigue load limit, axial
n _G	1.180 1/min	Limiting speed
n _{gr}	570 1/min	Reference speed
≈m	129,86 kg	Masa





Mounting dimensions

d _a min	420 mm	Minimum diameter shaft shoulder
D _a max	471 mm	Maximum diameter of housing shoulder
D _b min	550 mm	Minimum bore diameter housing
d _b max	340 mm	Maximum distance sleeve
d _{b1} max	324 mm	Maximum chamfer diameter of distance sleeve
r _a max	5 mm	Maximum recess radius
	30 °	Angle of chamfer of the distance sleeve

Dimensions

D ₁	392 mm	Bore diameter housing washer
d ₁	490 mm	Rip diameter shaft washer
r _{min}	6 mm	Minimum chamfer dimension
T ₁	70 mm	Height of the housing washer
T ₃	95 mm	Height of the shaft washer
T ₅	129,5 mm	Distance shaft washer - cage
A	175 mm	Distance of the center point

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



łożysko gabarytowe



Nieosiowość statyczna



Nieosiowość dynamiczna