



FAG




29464-E1-XL-THI

Axial spherical roller bearing

Axial spherical roller bearing 294...E1-XL, no flanging ring

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Heat treatment	Standard	Standard
Locating feature, housing washer	Without	
Cage	JP	Sheet metal cage
Handling thread holes	THI	Handling thread holes, shaft washer
Constricted width and inclination variation	Standard	
Test certificate	Without	

Main Dimensions & Performance Data

d	320 mm	Bore diameter
D	580 mm	Outside diameter
T	155 mm	Height
C _a	6.000.000 N	Basic dynamic load rating, axial
C _{0a}	19.100.000 N	Basic static load rating, axial
C _{ua}	1.790.000 N	Fatigue load limit, axial
n _G	1.090 1/min	Limiting speed
n _{gr}	530 1/min	Reference speed
≈m	162,5 kg	Masa



Mounting dimensions

d _{a min}	445 mm	Minimum diameter shaft shoulder
D _{a max}	507 mm	Maximum diameter of housing shoulder
D _{b min}	590 mm	Minimum bore diameter housing
d _{b max}	367 mm	Maximum distance sleeve
d _{b1 max}	346 mm	Maximum chamfer diameter of distance sleeve
r _{a max}	6 mm	Maximum recess radius
	30 °	Angle of chamfer of the distance sleeve

Dimensions

D ₁	422 mm	Bore diameter housing washer
d ₁	534,4 mm	Rip diameter shaft washer
r _{min}	7,5 mm	Minimum chamfer dimension
T ₁	74,5 mm	Height of the housing washer
T ₃	102 mm	Height of the shaft washer
T ₅	139,7 mm	Distance shaft washer - cage
A	191 mm	Distance of the center point

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia



łożysko gabarytowe



Nieosiowość statyczna



Nieosiowość dynamiczna