



FAG

30211-A>A

Tapered roller bearing

Tapered roller bearings 302, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	Standard	
Version code	>A	Not marked on bearing
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	100 mm	Outside diameter
B	21 mm	Width, inner ring
C	18 mm	Width, outer ring
T	22,75 mm	Width, total
C_r	91.000 N	Basic dynamic load rating, radial
C_{0r}	107.000 N	Basic static load rating, radial
C_{ur}	12.700 N	Fatigue load limit, radial
n_G	7.400 1/min	Limiting speed
n_{gr}	4.600 1/min	Thermal speed rating
$\approx m$	0,716 kg	Masa



Mounting dimensions

d a max	64 mm	Maximum diameter of shaft shoulder
d b min	64 mm	Minimum diameter of shaft shoulder
D a min	88 mm	Minimum diameter of housing shoulder
D a max	91 mm	Maximum diameter of housing shoulder
D b min	94 mm	Minimum diameter of housing shoulder
C a min	4 mm	Minimum axial space
C b min	4,5 mm	Minimum axial space
r a max	2 mm	Maximum fillet radius of shaft
r b max	1,5 mm	Maximum fillet radius of housing

Dimensions

r 1, 2 min	2 mm	Minimum chamfer dimension of inner ring back face
r 3, 4 min	1,5 mm	Minimum chamfer dimension of outer ring back face
a	21 mm	Distance between the apexes of the pressure cones
d 1	76,5 mm	Guidance rib diameter of inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Calculation factors

e	0,4	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,48	Dynamic axial load factor
Y 0	0,81	Static axial load factor

Additional information

T3DB055	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia