



FAG

30352-XL

Tapered roller bearing

Tapered roller bearings 303, main dimensions
acc. to DIN 720, separable

X-life

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	PN	Normal (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	XL	X-life
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	260 mm	Bore diameter
D	540 mm	Outside diameter
B	102 mm	Width, inner ring
C	85 mm	Width, outer ring
T	113 mm	Width, total
C _r	2.290.000 N	Basic dynamic load rating, radial
C _{0r}	2.600.000 N	Basic static load rating, radial
C _{ur}	280.000 N	Fatigue load limit, radial
n _G	1.600 1/min	Limiting speed
n _{gr}	820 1/min	Thermal speed rating
m	105,5 kg	Masa



Mounting dimensions

d a max	320 mm	Maximum diameter of shaft shoulder
d b min	286 mm	Minimum diameter of shaft shoulder
D a min	456 mm	Minimum diameter of housing shoulder
D a max	508 mm	Maximum diameter of housing shoulder
D b min	490 mm	Minimum diameter of housing shoulder
C a min	12 mm	Minimum axial space
C b min	28 mm	Minimum axial space
r a max	7,5 mm	Maximum fillet radius of shaft
r b max	6 mm	Maximum fillet radius of housing

Dimensions

r 1, 2 min	7,5 mm	Minimum chamfer dimension of inner ring back face
r 3, 4 min	6 mm	Minimum chamfer dimension of outer ring back face
a	96 mm	Distance between the apexes of the pressure cones
d 1	369,5 mm	Guidance rib diameter of inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	200 °C	Operating temperature max.

Calculation factors

e	0,35	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,73	Dynamic axial load factor
Y 0	0,95	Static axial load factor



Właściwości

-  Obciążenie promieniowe
-  Obciążenie osiowe jednokierunkowe
-  Smarowanie smarem
-  Smarowanie olejem
-  Bez uszczelnienia
-  Łożysko gabarytowe