




FAG

32912-H

Tapered roller bearing

Tapered roller bearings 329, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	P6X	Class 6X (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	H	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	85 mm	Outside diameter
B	17 mm	Width, inner ring
C	14 mm	Width, outer ring
T	17 mm	Width, total
C _r	46.600 N	Basic dynamic load rating, radial
C _{0r}	85.000 N	Basic static load rating, radial
C _{ur}	10.100 N	Fatigue load limit, radial
n _G	6.640 1/min	Limiting speed
n _{gr}	4.250 1/min	Thermal speed rating
≈m	315 g	Masa



Mounting dimensions

d a max	66 mm	Maximum diameter of shaft shoulder
d b min	66 mm	Minimum diameter of shaft shoulder
D a min	78 mm	Minimum diameter of housing shoulder
D a max	79 mm	Maximum diameter of housing shoulder
D b min	81 mm	Minimum diameter of housing shoulder
C a min	4 mm	Minimum axial space
C b min	3 mm	Minimum axial space
r a max	1 mm	Maximum fillet radius of shaft
r b max	1 mm	Maximum fillet radius of housing

Dimensions

r 1, 2 min	1 mm	Minimum chamfer dimension of inner ring back face
r 3, 4 min	1 mm	Minimum chamfer dimension of outer ring back face
a	16 mm	Distance between the apexes of the pressure cones
d 1 max	75,6 mm	Maximum guidance rib diameter of inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Calculation factors

e	0,33	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,81	Dynamic axial load factor
Y 0	1	Static axial load factor

Additional information

T2BC060	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia