



FAG

32913-H

Tapered roller bearing

Tapered roller bearings 329, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	P6X	Class 6X (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	H	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	65 mm	Bore diameter
D	90 mm	Outside diameter
B	17 mm	Width, inner ring
C	14 mm	Width, outer ring
T	17 mm	Width, total
C _r	47.000 N	Basic dynamic load rating, radial
C _{0r}	88.000 N	Basic static load rating, radial
C _{ur}	10.400 N	Fatigue load limit, radial
n _G	6.240 1/min	Limiting speed
n _{gr}	4.000 1/min	Thermal speed rating
≈m	323,78 g	Masa



Mounting dimensions

d _a max	71 mm	Maximum diameter of shaft shoulder
d _b min	71 mm	Minimum diameter of shaft shoulder
D _a min	83 mm	Minimum diameter of housing shoulder
D _a max	84 mm	Maximum diameter of housing shoulder
D _b min	86 mm	Minimum diameter of housing shoulder
C _a min	4 mm	Minimum axial space
C _b min	3 mm	Minimum axial space
r _a max	1 mm	Maximum fillet radius of shaft
r _b max	1 mm	Maximum fillet radius of housing

Dimensions

r _{1, 2} min	1 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4} min	1 mm	Minimum chamfer dimension of outer ring back face
a	17 mm	Distance between the apexes of the pressure cones
d ₁ max	80,8 mm	Maximum guidance rib diameter of inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

e	0,35	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,7	Dynamic axial load factor
Y ₀	0,93	Static axial load factor

Additional information

T2BC065	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia