




FAG

33015-H

Tapered roller bearing

Tapered roller bearings 330, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	P6X	Class 6X (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	H	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	75 mm	Bore diameter
D	115 mm	Outside diameter
B	31 mm	Width, inner ring
C	25,5 mm	Width, outer ring
T	31 mm	Width, total
C _r	132.000 N	Basic dynamic load rating, radial
C _{0r}	232.000 N	Basic static load rating, radial
C _{ur}	30.500 N	Fatigue load limit, radial
n _G	4.720 1/min	Limiting speed
n _{gr}	3.700 1/min	Thermal speed rating
≈m	1,16 kg	Masa



Mounting dimensions

$d_{a \max}$	83 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	82 mm	Minimum diameter of shaft shoulder
$D_{a \min}$	104 mm	Minimum diameter of housing shoulder
$D_{a \max}$	108 mm	Maximum diameter of housing shoulder
$D_{b \min}$	110 mm	Minimum diameter of housing shoulder
$C_{a \min}$	6 mm	Minimum axial space
$C_{b \min}$	5,5 mm	Minimum axial space
$r_{a \max}$	1,5 mm	Maximum fillet radius of shaft
$r_{b \max}$	1,5 mm	Maximum fillet radius of housing

Dimensions

$r_{1, 2 \min}$	1,5 mm	Minimum chamfer dimension of inner ring back face
$r_{3, 4 \min}$	1,5 mm	Minimum chamfer dimension of outer ring back face
a	23 mm	Distance between the apexes of the pressure cones
$d_{1 \max}$	98,8 mm	Maximum guidance rib diameter of inner ring

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Calculation factors

e	0,3	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y	2,01	Dynamic axial load factor
Y_0	1,11	Static axial load factor

Additional information

T2CE075

Comparative designation to ISO 10317 and ISO 355



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia