



FAG





X-life

3305-BD-XL-TVH-L285

Angular contact ball bearing

Angular contact ball bearing 33...BD-XL-TVH, double row, X-life, plastic cage

Informacje techniczne



Twoja aktualna wersja produktu

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Type of Seal	Without	Not sealed
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	L285	Grease (L285/customer specific)
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D	62 mm	Outside diameter
B	25,4 mm	Width
C _r	31.500 N	Basic dynamic load rating, radial
C _{0r}	21.000 N	Basic static load rating, radial
C _{ur}	1.460 N	Fatigue load limit, radial
n _G	12.400 1/min	Limiting speed
n _{gr}	9.400 1/min	Reference speed
m	0,343 kg	Masa



Mounting dimensions

$d_{a \min}$	32 mm	Minimum diameter shaft shoulder
$D_{a \max}$	55 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
D_1	51,47 mm	Shoulder diameter outer ring
D_2	53,72 mm	Caliber diameter outer ring
d_1	39,5 mm	Shoulder diameter inner ring
d_2	37,63 mm	Caliber diameter inner ring
a	35,4 mm	Distance between the apexes of the pressure cones
α	30 °	Contact angle

Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

Właściwości

	Obciążenie promieniowe
	Obciążenie osiowe jednokierunkowe
	Obciążenie osiowe dwukierunkowe
	Smarowanie smarem
	Bez uszczelnienia