FAG

# 3306-BD-XL

Angular contact ball bearing

Angular contact ball bearing 33..-BD-XL,
double row, X-life, steel sheet metal cage

X-life

## Informacje techniczne







### Twoja aktualna wersja produktu

| | | |
|---|---|---|
| Design variant | B | Bearing without filling slot |
| Changed internal design | D | D |
| Sealing | Without | Not sealed |
| Cage | JH | Steel sheet metal |
| Tolerance class | P6 | Class 6 (ISO 492:2023) |
| Dimensional / heat stabilization | SN | Rings dimensional stabilized up to 120° |
| Lubricant | Without | Bearing not greased |
| Axial internal clearance | CN | Group N (CN) |

### Main Dimensions & Performance Data

| | | |
|---|---|---|
| d | 30 mm | Bore diameter |
| D | 72 mm | Outside diameter |
| B | 30,2 mm | Width |
| $C_r$ | 43.000 N | Basic dynamic load rating, radial |
| $C_{0r}$ | 29.500 N | Basic static load rating, radial |
| $C_{ur}$ | 2.050 N | Fatigue load limit, radial |
| $n_G$ | 10.400 1/min | Limiting speed |
| $n_{\vartheta r}$ | 8.500 1/min | Reference speed |
| ≈m | 0,55 kg | Masa |

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje

## Mounting dimensions

| | | |
|---|---|---|
| $d_{a\ min}$ | 37 mm | Minimum diameter shaft shoulder |
| $D_{a\ max}$ | 65 mm | Maximum diameter of housing shoulder |
| $r_{a\ max}$ | 1 mm | Maximum fillet radius |

## Dimensions

| | | |
|---|---|---|
| $r_{min}$ | 1,1 mm | Minimum chamfer dimension |
| $D_1 \approx$ | 60,47 mm | Shoulder diameter outer ring |
| $D_2 \approx$ | 63,46 mm | Caliber diameter outer ring |
| $d_1 \approx$ | 46,25 mm | Shoulder diameter inner ring |
| $d_2 \approx$ | 44,35 mm | Caliber diameter inner ring |
| $a \approx$ | 41,9 mm | Distance between the apexes of the pressure cones |
| $\alpha$ | 30 ° | Contact angle |

## Temperature range

| | | |
|---|---|---|
| $T_{min}$ | -30 °C | Operating temperature min. |
| $T_{max}$ | 120 °C | Operating temperature max. |

## Właściwości

- Obciążenie promieniowe
- Obciążenie osiowe jednokierunkowe
- Obciążenie osiowe dwukierunkowe
- Smarowanie smarem
- Smarowanie olejem
- Bez uszczelnienia

Karta katalogowa jest jedynie przeglądem wymiarów i podstawowych nośności wybranego produktu. Zawsze należy stosować się do wszystkich dalszych informacji i instrukcji dotyczących tego produktu. Na naszej stronie internetowej znajduje się formularz kontaktowy umożliwiający wysłanie zapytania o dalsze informacje