



FAG

33216-H

Tapered roller bearing

Tapered roller bearings 332, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	P6X	Class 6X (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	H	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	80 mm	Bore diameter
D	140 mm	Outside diameter
B	46 mm	Width, inner ring
C	35 mm	Width, outer ring
T	46 mm	Width, total
C _r	238.000 N	Basic dynamic load rating, radial
C _{0r}	380.000 N	Basic static load rating, radial
C _{ur}	48.000 N	Fatigue load limit, radial
n _G	3.840 1/min	Limiting speed
n _{gr}	3.200 1/min	Thermal speed rating
m	2,93 kg	Masa



Mounting dimensions

d _a max	89 mm	Maximum diameter of shaft shoulder
d _b min	90 mm	Minimum diameter of shaft shoulder
D _a min	119 mm	Minimum diameter of housing shoulder
D _a max	130 mm	Maximum diameter of housing shoulder
D _b min	135 mm	Minimum diameter of housing shoulder
C _a min	7 mm	Minimum axial space
C _b min	11 mm	Minimum axial space
r _a max	2,5 mm	Maximum fillet radius of shaft
r _b max	2 mm	Maximum fillet radius of housing

Dimensions

r _{1, 2} min	2,5 mm	Minimum chamfer dimension of inner ring back face
r _{3, 4} min	2 mm	Minimum chamfer dimension of outer ring back face
a	35 mm	Distance between the apexes of the pressure cones
d ₁ max	114,6 mm	Maximum guidance rib diameter of inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.

Calculation factors

e	0,43	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,41	Dynamic axial load factor
Y ₀	0,78	Static axial load factor

Additional information

T3EE080	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia