




FAG

33218-H

Tapered roller bearing

Tapered roller bearings 332, main dimensions
acc. to DIN 720, separable

Informacje techniczne



Twoja aktualna wersja produktu

Tolerance class	P6X	Class 6X (ISO 492:2023)
Heat treatment	Standard	
Cage	Standard	Sheet steel cage, window cage, roller-guided
Internal design	Standard	
Quality level	H	
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	90 mm	Bore diameter
D	160 mm	Outside diameter
B	55 mm	Width, inner ring
C	42 mm	Width, outer ring
T	55 mm	Width, total
C _r	333.000 N	Basic dynamic load rating, radial
C _{0r}	520.000 N	Basic static load rating, radial
C _{ur}	63.000 N	Fatigue load limit, radial
n _G	3.360 1/min	Limiting speed
n _{gr}	3.000 1/min	Thermal speed rating
≈m	4,67 kg	Masa



Mounting dimensions

d a max	101 mm	Maximum diameter of shaft shoulder
d b min	100 mm	Minimum diameter of shaft shoulder
D a min	135 mm	Minimum diameter of housing shoulder
D a max	150 mm	Maximum diameter of housing shoulder
D b min	154 mm	Minimum diameter of housing shoulder
C a min	9 mm	Minimum axial space
C b min	13 mm	Minimum axial space
r a max	2,5 mm	Maximum fillet radius of shaft
r b max	2 mm	Maximum fillet radius of housing

Dimensions

r 1, 2 min	2,5 mm	Minimum chamfer dimension of inner ring back face
r 3, 4 min	2 mm	Minimum chamfer dimension of outer ring back face
a	41 mm	Distance between the apexes of the pressure cones
d 1 max	127,3 mm	Maximum guidance rib diameter of inner ring

Temperature range

T min	-30 °C	Operating temperature min.
T max	120 °C	Operating temperature max.

Calculation factors

e	0,42	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y	1,43	Dynamic axial load factor
Y 0	0,78	Static axial load factor

Additional information

T3FE090	Comparative designation to ISO 10317 and ISO 355
---------	--



Właściwości



Obciążenie promieniowe



Obciążenie osiowe jednokierunkowe



Smarowanie smarem



Smarowanie olejem



Bez uszczelnienia